

THK Automotive Pte Ltd
Dump Mechanism








MODEL	KRM-220L	KRM-220A	KRM-201	KRM-183	KRM-160C	KRM-160S	KRM-143
L (mm)	1900	1740	1765	1720	1640	1330	1045
W (mm)	630	560	590	550	520	430	415
H (mm)	500	420	470	410	340	320	390
X (mm)	520	520	520	480	480	480	380
Weight (kg)	750	640	550	520	370	240	130

MODEL	KRM-220L	KRM-220A	KRM-201	KRM-183	KRM-160C	KRM-160S	KRM-143
Recommended Payload (tons)	28 to 35	28 to 35	25 to 32	21 to 28	14 to 16	9 to 12	6 to 9
Body Length (mm)	8	6	6	5.3	4.9	4.2	3.5
Rear Overhang (mm)	1050	1050	900	900	800	800	600
Load Center to Hinge (mm)	2950	2100	2100	1750	1650	1400	1100
Trunion to Hinge (mm)	3100	2600	2500	2480	1720	1600	1100
Rated Lifting Cap (tons)	35	35	16 to 18	15 to 17	6 to 8	5 to 6	4 to 5
Design Lifting Cap (tons)	50	50	29	27	16	12	9

MODEL	KP 1505	KP 1403/05	KP 75	KP 551	KP 45	KP 35
Discharge Volume (cc/rev)	150	136	72	55	45	35
Max Testing Pressure (kg/cm ²)	210	210	200	150	150	140
Standard Revolution (rpm)	1000	1000	1000	1000	1000	1000
Gross Weight (kg)	38	37	21	14	12	10

Accessories

	
<p>KP 1405 Adapter (FC 1405)</p>	<p>KP 551 Adaptor (FC 551)</p>
	
<p>Drive Shaft (4T / 10T)</p>	<p>Piping</p>
	
<p>Hinge Bracket</p>	